

CLAIM AMENDMENTS

1. (CANCELED)
2. (CANCELED)
3. (CANCELED)
4. (CANCELED)
5. (CANCELED)
6. (CANCELED)
7. (CANCELED)
8. (CANCELED)
9. (CANCELED)
10. (CANCELED)
11. (CANCELED)
12. (CANCELED)
13. (CANCELED)
14. (CANCELED)
15. (CANCELED)
16. (CANCELED)
17. (CANCELED)
18. (CANCELED)
19. (CANCELED)
20. (CANCELED)
21. (CANCELED)
22. (CANCELED)
23. (CANCELED)
24. (CANCELED)
25. (CANCELED)
26. (CANCELED)
27. (CANCELED)
28. (CANCELED)
29. (CANCELED)
30. (CANCELED)
31. (CANCELED)
32. (CANCELED)
33. (CANCELED)

34. (CANCELED)
35. (CANCELED)
36. (CANCELED)
37. (CANCELED)
38. (CANCELED)
39. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:
 - a section of material;
 - a plurality of pairing members;
 - a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a tightening member and a handle portion for holding said fastening members while attaching said fastening members to said structure; and
 - a means for entrance and exit;
 - wherein said pairing members are connected to said material; and
 - wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.
40. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:
 - a section of material;
 - a plurality of pairing members;
 - a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a hooked portion for grasping an edge of said structure; and
 - a means for entrance and exit;
 - wherein said pairing members are connected to said material; and
 - wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.
41. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;
a plurality of pairing members;
a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a tightening member that works in conjunction with a hooked portion to hold an edge of said support structure; and

a means for entrance and exit;
wherein said pairing members are connected to said material; and
wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

42. (CANCELED)

43. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;
a plurality of pairing members;
a plurality of fastening members for fastening said material to a support structure by said pairing members;

a plurality of hanging members at a border of said section of material, said hanging members being selectively attachable from said border of said section of material; and

a means for entrance and exit;
wherein said pairing members are connected to said material; and
wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

44. (CANCELED)

45. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;
a plurality of pairing members;
a plurality of fastening members for fastening said material to a support structure by said pairing members;

a plurality of hanging members at a border of said section of material said hanging members comprising a projection having an end, said end adapted for removable connection to a lifting device; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with said section of material.

46. (PREVIOUSLY AMENDED) The apparatus of claim 45, wherein said lifting device comprises a pole.

47. (CANCELED)

48. (CANCELED)

49. (CANCELED)

50. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members said pairing members comprising a rivet;

a plurality of fastening members for fastening said material to a support structure by said pairing members; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

51. (CANCELED)

52. (CANCELED)

53. (PREVIOUSLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members; and

a means for entrance and exit, said entrance and exit means being securable by a belt;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

54. (CANCELED)